

BCS-TQE5200IR3-G(-B)



2Mpx IR bullet camera HDCVI/AHD/TVI/ANALOG with 2.8~13.5mm lens



Key features

- Sensor 1/2.9" 2Mpx SONY IMX323 CMOS + V30E
- Resolution up to 1920x1080(1080P)
- 4 system camera: HDCVI/TVI/AHD/ANALOG
- IR-cut filter with auto switch (ICR)
- Digital Noise Reduction DNR
- Functions AGC, AES, BLC, D-WDR
- Menu available through BCS recorder
- Varifocal lens 2.8~13.5mm
- IR Led distance up to 50m
- IR Led life time up to 50 000 hours
- System change switch
- Easy adjustment and installation
- Metal case protection IP66
- Power supply 12V DC

BCS-TQE5200IR3-B – version with white case

Specification

Model		BCS-TQE5200IR3-G(-B)
System		HDCVI/TVI/AHD/ANALOG
Sensor		1/2.9" 2Mpx SONY IMX323 CMOS + V30E
Pixels		1920(H) x 1080(V)
Video out		1 V p-p, composite, BNC, 75 Ohm
Resolution		1920x1080
Minimum illumination		0 Lux/F1.3 (IR On)
S/N ratio		> 50dB (AGC Off)
White balance		(AWB) Auto/manual
Basic functions	Lens	2.8~13.5mm
	Backlight compensation	BLC / D-WDR
	Shutter	Auto/manual (1/50-1/10000s),
	Gain control	(AGC) Auto/manual
	Noise reduction	Auto/manual
	Day/night	IR-cut filter with auto switch (ICR)
	IR Led distance	Up to 50m – 4 x LED IR3
Power supply		12V DC
Power consumption		<6,5W
Working environment		-30°C ~ +60°C
Weight		0,81kg
Dimensions		77mm x 286mm

Dimensions

